
| | |
|---|---|
| article# | **80132-9** |
| article description | **CEE angled plug 16A 3p 9h IP67 TWIST** |
| description long | CEE angled plug 16A 3p 9h IP67 TWIST<br>housing material: PA6<br>rated current: 16A<br>number of poles: 3 (2P+PE)<br>clock-position: 9h<br>rated voltage/frequency: 380-415V~ / 50+60Hz<br>contacts: brass<br>connection technology: screw terminals<br>IP protection class: IP67 |
| GTIN (EAN) | 9003399487651 |
| country of origin | AT |
| customs number | 85366990 |
| net weight | 0.128 kg |
| packaging quantitiy | 10 |
| minimum order quantitiy | 10 |



| | |
|---|---|
| ETIM 10.0 | EC000140 |
| IEC-amperage | 16 A |
| Number of poles | 3 |
| Voltage according to EN 60309-2 | 380-415 V (50+60 Hz) red |
| Clock hour position | 9 h |
| Identification colour | Red |
| Degree of protection (IP) | IP67 |
| Connection system | Screwed terminal |
| Cable entry | Gland nut |
| Suitable for cable diameter | 6 – 15 mm |
| Angle of plug | Angled |
| Material | Plastic |
| Contact material | CuZn |
| Surface treatment contacts | Untreated |




| | |
|---|---|
| a | 98 mm |
| b | 71 mm |
| c | 92 mm |
| d | 15 ° |
| K (cable Ø) | 6-15 mm |
| SW | 38 mm |
| wire flexible | 1-2,5 mm² |
| contact screws | 100 Ncm |
| strain relief | 500 Ncm |
| dismantling length | 50 mm |
| stripping length | 10-12 mm |
| ambient temperature | -25 – 40 °C |
| temperature resistance | -25 – 80 °C |

https://www.pcelectric.at/shop/en/?func=detail&artnr=80132-9

Changes and printing errors reserved!

3/18/2026