
article#	**0339-4**
article description	**CEE-plug 60A 2P3W 4h IP69k UL**
description long	CEE-plug 60A 2P3W 4h IP69k UL (PCE360P4W) housing material: PA6 rated current: 60A number of poles: 2P3W (3p) clock position: 4h rated voltage: 120VAC contacts: brass nickel plated connection technology: frame terminals with screws IP rating: IP6X, X6, X7, X9k (watertight) UL type: 4, 4X HP-rating (locked rotor): 2 according to UL1682 and IEC/EN 60309-2 (SERIES II) UL-product category: QLHN / QLHN7 UL-file number: E232901
GTIN (EAN)	9003399719455
country of origin	AT
customs number	85366990
net weight	0.601 kg
packaging quantitiy	2
minimum order quantitiy	2





ETIM 10.0	EC000140
Amperage according to UL/CSA (for UL-version)	60 A
Number of poles	3
Voltage according to EN 60309-2	Other
Clock hour position	4 h
Identification colour	Yellow
Degree of protection (IP)	IP67
Connection system	Screwed terminal
Cable entry	Gland nut
Angle of plug	Straight
Material	Plastic
Contact material	CuZn
Surface treatment contacts	Nickel-plated



a	10.24 inch
b	4.53 inch
K (cable Ø)	0.59-1.46 inch
SW	2.44 inch
wire flexible	10-4 AWG
contact screws	17.7 lbf-in
housing screws	17.7 lbf-in
strain relief	nut 66 lbf-in / clamp 14.2 lbf-in
dismantling length	3.94 inch
stripping length	0.59-0.71 inch
temperature resistance	-13 – 176 °F

https://www.pcelectric.at/shop/en/?func=detail&artnr=0339-4

Changes and printing errors reserved!

8/10/2026