
article#	**3259-9f7**
article description	**CEE-receptacle flange 75x75 straight 30A 4P5W 9h IP44 UL**
description long	CEE-receptacle flange 75x75 straight 30A 4P5W 9h IP44 UL (PCE530R9S) housing material: PA6 rated current: 32A/30A number of poles: 4P5W (5p) clock position: 9h rated voltage: 120/208VAC contacts: brass connection technology: screw terminals dimensions (flange/fixing center): 75x75mm / 60x60mm IP protection class: IP44 according to UL1682 und IEC/EN 60309-2 (SERIE II) UL-product category: QLIW / QLIW7 UL-file number: E252008
GTIN (EAN)	9003399438158
country of origin	AT
customs number	85366990
net weight	0.210 kg
packaging quantitiy	10
minimum order quantitiy	10



ETIM 9.0	EC001317
IEC-amperage	32 A
Amperage according to UL/CSA (for UL-version)	30 A
Number of poles	5
Clock hour position	9 h
Identification colour	Blue
Degree of protection (IP)	IP44
Connection system	Screwed terminal
Angle of plug	Straight
Material	Plastic
Contact material	CuZn
Surface treatment contacts	Untreated
Flange size vertical	75 mm
Drill hole distance vertical	60 mm
Flange size horizontal	75 mm
Drill hole distance horizontal	60 mm



a	2.95 inch
b	2.95 inch
c	2.36 inch
d	2.36 inch
e	0.91 inch
f	2.64 inch
g	0.22 inch
h	2.28 inch
i	4.25 inch
j	5.35 inch
wire flexible	14-10 AWG
wire solid	2,5-10 mm²
contact screws	9.74 lbf-in
dismantling length	1.97 inch
stripping length	0.47-0.55 inch
temperature resistance	-13 – 176 °F

https://www.pcelectric.at/shop/en/?func=detail&artnr=3259-9f7

Changes and printing errors reserved!

8/18/2025