
| | |
|---|---|
| article# | **6139-5v** |
| article description | **CEE-inlet flange 70x70 straight 20A 2P3W 5h IP44 UL** |
| description long | CEE-inlet flange 70x70 straight 20A 2P3W 5h IP44 UL (PCE320B5Sv)<br>housing material: PA6<br>rated current: 20A<br>number of poles: 2P3W (3p)<br>clock position: 5h<br>rated voltage: 277VAC<br>contacts: brass nickel plated<br>connection technology: screw terminals<br>dimensions (flange/fixing center): 70x70mm / 56x56mm<br>IP protection class: IP44<br>according to UL1682<br>UL-product category: QLIW / QLIW7<br>UL-file number: E252008 |
| country of origin | AT |
| customs number | 85366990 |
| packaging quantitiy | 10 |
| minimum order quantitiy | 10 |



| | |
|---|---|
| ETIM 9.0 | EC001319 |
| Amperage according to UL/CSA (for UL-version) | 20 A |
| Number of poles | 3 |
| Clock hour position | 5 h |
| Identification colour | Grey |
| Degree of protection (IP) | IP44 |
| Connection system | Screwed terminal |
| Construction type | Built-up device plug |
| Angle of plug | Angled |
| Material | Plastic |
| Contact material | CuZn |
| Surface treatment contacts | Nickel-plated |




| | |
|---|---|
| a | 2.76 inch |
| b | 2.76 inch |
| c | 2.20 inch |
| d | 2.20 inch |
| e | 0.83 inch |
| f | 1.65 inch |
| g | 0.22 inch |
| h | 1.69 inch |
| wire flexible | 16-12 AWG |
| wire solid | 1-4 mm² |
| contact screws | 8.85 lbf-in |
| dismantling length | 1.97 inch |
| stripping length | 0.39-0.47 inch |
| temperature resistance | -13 – 176 °F |

https://www.pcelectric.at/shop/en/?func=detail&artnr=6139-5v

Changes and printing errors reserved!

2/23/2026