
article#	**6349-12**
article description	**CEE-inlet flange 100x100 straight 60A 3P4W 12h IP69k UL**
description long	CEE-inlet flange 100x100 straight 60A 3P4W 12h IP69k UL (PCE460B12W) housing material: PA6 rated current: 60A number of poles: 3P4W (4p) clock position: 12h rated voltage: 120/250VAC single phase contacts: brass nickel plated connection technology: frame terminals with screws IP rating: IP6X, X6, X7, X9k (watertight) UL type: 4, 4X HP-rating (locked rotor): 2/3 according to UL1682 and IEC/EN 60309-2 (SERIES II) UL-product category: QLIW / QLIW7 UL-file number: E252008
country of origin	AT
customs number	85366990
net weight	0.497 kg
packaging quantitiy	2
minimum order quantitiy	2



ETIM 9.0	EC001319
Amperage according to UL/CSA (for UL-version)	60 A
Voltage according to EN 60309-2	125/250 V AC orange
Number of poles	4
Clock hour position	12 h
Identification colour	Orange
Degree of protection (IP)	IP69K
Connection system	Screwed terminal
Construction type	Built-up device plug
Angle of plug	Straight
Material	Plastic
Contact material	CuZn
Surface treatment contacts	Nickel-plated



a	3.94 inch
b	3.94 inch
c	3.15 inch
d	3.15 inch
e	0.31 inch
f	4.29 inch
g	4.53 inch
h	3.03 inch
i	0.28 inch
wire flexible	10-4 AWG
contact screws	17.7 lbf-in
connecting screws	17.7 lbf-in
stripping length	0.59-0.71 inch
temperature resistance	-13 – 176 °F

https://www.pcelectric.at/shop/en/?func=detail&artnr=6349-12

1/20/2026 Changes and printing errors reserved!