
article#	**11492-7**
article description	**CEE-receptacle wall mount 20A 3P4W 7h IP67 UL**
description long	CEE-receptade wall mount 20A 3P4W 7h IP67 UL (PCE420RS7W) housing material: PA6 rated current: 20A number of poles: 3P4W (4p) clock position: 7h rated voltage: 480VAC contacts: brass connection technology: screw terminals IP protection class: IP67 according to UL1682 UL-product category: QLIW / QLIW7 UL-file number: E252008
GTIN (EAN)	9003399231483
country of origin	AT
customs number	85366990
net weight	0.241 kg
packaging quantitiy	5
minimum order quantitiy	5



ETIM 9.0	EC001321
Mounting method	Surface mounted
Amperage according to UL/CSA (for UL-version)	20 A
Clock hour position	7 h
Identification colour	Red
Degree of protection (IP)	IP67
Connection system	Screwed terminal
Cable entry	Gland nut
Material	Plastic
Contact material	CuZn
Surface treatment contacts	Untreated
Type of fastening	External mounting



a	5.87 inch
b	3.90 inch
wire flexible	16-12 AWG
wire solid	1-4 mm²
contact screws	8.85 lbf-in
connecting screws	9.74 lbf-in
dismantling length	1.97 inch
stripping length	0.39-0.47 inch
temperature resistance	-13 – 176 °F

https://www.pcelectric.at/shop/en/?func=detail&artnr=11492-7

Changes and printing errors reserved!

2/23/2026