
article#	**11391-4**
article description	**CEE-receptacle wall mount 20A 2P3W 4h IP44 UL**
description long	CEE-receptade wall mount 20A 2P3W 4h IP44 UL (PCE320RS4S) housing material: PA6 rated current: 16A/20A number of poles: 2P3W (3p) clock position: 4h rated voltage: 120VAC contacts: brass connection technology: screw terminals IP protection class: IP44 according to UL1682 und IEC/EN 60309-2 (SERIE II) UL-product category: QLIW / QLIW7 UL-file number: E252008
GTIN (EAN)	9003399947223
country of origin	AT
customs number	85366990
net weight	0.210 kg
packaging quantitiy	5
minimum order quantitiy	5



ETIM 9.0	EC001321
Mounting method	Surface mounted
IEC-amperage	16 A
Amperage according to UL/CSA (for UL-version)	20 A
Clock hour position	4 h
Identification colour	Yellow
Degree of protection (IP)	IP44
Connection system	Screwed terminal
Cable entry	Gland nut
Material	Plastic
Contact material	CuZn
Surface treatment contacts	Untreated
Type of fastening	External mounting



a	5.63 inch
b	3.98 inch
wire flexible	16-12 AWG
wire solid	1-4 mm²
contact screws	8.85 lbf-in
connecting screws	9.74 lbf-in
dismantling length	1.97 inch
stripping length	0.39-0.47 inch
temperature resistance	-13 – 176 °F

https://www.pcelectric.at/shop/en/?func=detail&artnr=11391-4

Changes and printing errors reserved!

2/23/2026