
article#	**25712-src**
article description	**Safety connector lid nat SH IP54 red series TopTaurus2**
description long	Safety connector series TopTaurus2 with hinged lid color: black-red, material: PA6 2-component rubberized screwless quick lock system for housing cover and strain relief earthing system: Austrian/German with shutter 16A/ 250V AC / 3p (2P+E), protection rating: IP54
GTIN (EAN)	9003399482496
country of origin	AT
customs number	85366990
net weight	0.133 kg
packaging quantitiy	10
minimum order quantitiy	10





ETIM 10.0	EC001327
Model	Coupler with protective contact CEE 7/3 (type F)
Material	Plastic
Material quality	Thermoplastic
Degree of protection (IP)	IP54
Insert direction	Straight
Connection system	Screwed terminal
With quick-lock	True
Colour	Red
Number of poles	3
Nominal voltage	250 V
Nominal current	16 A
For heavy conditions according to VDE	True

K (cable Ø)	6-14 mm
SW	21 mm
wire flexible	1-2,5 mm²
contact screws	80 Ncm
strain relief	400 Ncm
dismantling length	30 mm
stripping length	7 mm
ambient temperature	-25 – 40 °C



https://www.pcelectric.at/shop/en/?func=detail&artnr=25712-src

Changes and printing errors reserved!

3/19/2026