
article#	**61592-9v**
article description	**CEE-inlet flange 75x75 straight 20A 4P5W 9h IP67 UL**
description long	CEE-inlet flange 75x75 straight 20A 4P5W 9h IP67 UL (PCE520B9Wv) housing material: PA6 rated current: 16A/20A number of poles: 4P5W (5p) clock position: 9h rated voltage: 120/208VAC contacts: brass nickel plated connection technology: screw terminals dimensions (flange/fixing center): 75x75mm / 60x60mm IP protection class: IP67 according to UL1682 und IEC/EN 60309-2 (SERIE II) UL-product category: QLIW / QLIW7 UL-file number: E252008
country of origin	AT
customs number	85366990
packaging quantitiy	10
minimum order quantitiy	10



ETIM 9.0	EC001319
IEC-amperage	16 A
Amperage according to UL/CSA (for UL-version)	20 A
Number of poles	5
Clock hour position	9 h
Identification colour	Blue
Degree of protection (IP)	IP67
Connection system	Screwed terminal
Construction type	Built-up device plug
Angle of plug	Angled
Material	Plastic
Contact material	CuZn
Surface treatment contacts	Nickel-plated



a	2.95 inch
b	2.95 inch
c	2.36 inch
d	2.36 inch
e	0.51 inch
f	1.89 inch
g	0.22 inch
h	2.17 inch
i	3.43 inch
x	0.20 inch
wire flexible	16-12 AWG
wire solid	1-4 mm²
contact screws	8.85 lbf-in
dismantling length	1.97 inch
stripping length	0.39-0.47 inch
temperature resistance	-13 – 176 °F

https://www.pcelectric.at/shop/en/?func=detail&artnr=61592-9v

Changes and printing errors reserved!

2/23/2026