
article#	**32592-7v**
article description	**CEE-receptacle flange 75x75 straight 30A 4P5W 7h IP67 UL**
description long	CEE-receptacle flange 75x75 straight 30A 4P5W 7h IP67 UL (PCE530R7Wv) housing material: PA6 rated current: 30A number of poles: 4P5W (5p) clock position: 7h rated voltage: 277/480VAC contacts: brass nickel plated connection technology: screw terminals dimensions (flange/fixing center): 75x75mm / 60x60mm IP protection class: IP67 according to UL1682 UL-product category: QLIW / QLIW7 UL-file number: E252008
GTIN (EAN)	9003399665585
country of origin	AT
customs number	85366990
net weight	0.260 kg
packaging quantitiy	10
minimum order quantitiy	10



ETIM 9.0	EC001317
Amperage according to UL/CSA (for UL-version)	30 A
Number of poles	5
Clock hour position	7 h
Identification colour	Red
Degree of protection (IP)	IP67
Connection system	Screwed terminal
Angle of plug	Straight
Material	Plastic
Contact material	CuZn
Surface treatment contacts	Nickel-plated
Flange size vertical	75 mm
Drill hole distance vertical	60 mm
Flange size horizontal	75 mm
Drill hole distance horizontal	60 mm



a	2.95 inch
b	2.95 inch
c	2.36 inch
d	2.36 inch
e	0.91 inch
f	2.80 inch
g	0.22 inch
h	2.28 inch
i	5.12 inch
j	5.35 inch
wire flexible	14-10 AWG
wire solid	2,5-10 mm²
contact screws	9.74 lbf-in
dismantling length	1.97 inch
stripping length	0.47-0.55 inch
temperature resistance	-13 – 176 °F

https://www.pcelectric.at/shop/en/?func=detail&artnr=32592-7v

Changes and printing errors reserved!

8/18/2025