

article#	**633-4**
article description	**CEE-flanged plug straight 63A 3p 4h IP67 POWER TWIST**
description long	CEE-flanged plug straight 63A 3p 4h IP67 POWER TWIST housing material: PA6 rated current: 63A number of poles: 3 (2P+PE) clock-position: 4h rated voltage/frequency: 100-130V~ / 50+60Hz contacts: brass nickel plated, with pilot pin connection technology: frame terminals with screws dimensions (flange/fixing center): 100x100 mm / 80x80 mm IP protection class: IP66/IP67
GTIN (EAN)	9003399072185
country of origin	AT
customs number	85366990
net weight	0.479 kg
packaging quantitiy	2
minimum order quantitiy	2



ETIM 9.0	EC001319
IEC-amperage	63 A
Voltage according to EN 60309-2	110 V (50+60 Hz) yellow
Number of poles	3
Clock hour position	4 h
Identification colour	Yellow
Degree of protection (IP)	IP67
Connection system	Screwed terminal
Construction type	Built-up device plug
Angle of plug	Straight
Material	Plastic
Contact material	CuZn
Surface treatment contacts	Nickel-plated



a	100 mm
b	100 mm
c	80 mm
d	80 mm
e	8 mm
f	109 mm
g	115 mm
h	77 mm
i	7 mm
wire flexible	6-16 mm²
wire solid	6-25 mm²
contact screws	200 Ncm
connecting screws	200 Ncm
dismantling length	100 mm
stripping length	15-18 mm
ambient temperature	-25 – 40 °C
temperature resistance	-25 – 80 °C

https://www.pcelectric.at/shop/en/?func=detail&artnr=633-4

Changes and printing errors reserved!

8/1/2023