
| | |
|---|---|
| article# | **5149-5** |
| article description | **CEE-inlet wall mount 20A 3P4W 5h IP44 UL** |
| description long | CEE-inlet wall mount 20A 3P4W 5h IP44 UL (PCE420BS5S)<br>housing material: PA6<br>rated current: 20A<br>number of poles: 3P4W (4p)<br>clock position: 5h<br>rated voltage: 600VAC<br>contacts: brass<br>connection technology: screw terminals<br>IP protection class: IP44<br>according to UL1682<br>UL-product category: QLIW / QLIW7<br>UL-file number: E252008 |
| GTIN (EAN) | 9003399584220 |
| country of origin | AT |
| customs number | 85366990 |
| net weight | 0.183 kg |
| packaging quantitiy | 10 |
| minimum order quantitiy | 10 |



| | |
|---|---|
| ETIM 9.0 | EC001319 |
| Amperage according to UL/CSA (for UL-version) | 20 A |
| Number of poles | 4 |
| Clock hour position | 5 h |
| Identification colour | Black |
| Degree of protection (IP) | IP44 |
| Connection system | Screwed terminal |
| Construction type | Surface mounted device plug |
| Angle of plug | Angled |
| Material | Plastic |
| Contact material | CuZn |
| Surface treatment contacts | Untreated |




| | |
|---|---|
| a | 4.76 inch |
| b | 2.99 inch |
| wire flexible | 16-12 AWG |
| wire solid | 1-4 mm² |
| contact screws | 8.85 lbf-in |
| housing screws | 9.74 lbf-in |
| connecting screws | 9.74 lbf-in |
| dismantling length | 1.97 inch |
| stripping length | 0.39-0.47 inch |
| temperature resistance | -13 – 176 °F |

https://www.pcelectric.at/shop/en/?func=detail&artnr=5149-5

Changes and printing errors reserved!

2/23/2026