
article#	**253811-soc5**
article description	**3-way connector TopTaurus2 rubber cap with band nat SH 5p IP54 orange**
description long	3-way connector TopTaurus2 rubber with cap color housing/terminal-cover: black/orange contact carrier: polyamide ready wired on 5-pole terminal block (PH1) earthing system: Austrian/German with shutter (type F - with earth lug) contacts: nickel plated 250V~ / 16A / 2P+E external strain relief with gland nut for serve conditions protection rating: IP54
country of origin	AT
customs number	85366990
packaging quantitiy	5
minimum order quantitiy	50





ETIM 10.0	EC001327
Model	Coupler with protective contact CEE 7/3 (type F)
Material	Rubber
Material quality	Thermoplastic
Degree of protection (IP)	IP54
Insert direction	Straight
Connection system	Screwed terminal
Colour	Orange
Number of poles	3
Nominal voltage	250 V
Nominal current	16 A
For heavy conditions according to VDE	True



K (cable Ø)	6-19 mm
wire flexible	1-2,5 mm²
contact screws	50 Ncm
housing screws	160 Ncm
strain relief	400 Ncm
dismantling length	30 mm
stripping length	7 mm
ambient temperature	-25 – 40 °C
IK-code *)	IK10

*) The IK-test is not part of the IEC 60309 standard for industrial plugs and socket-outlets or the IEC 60884 standard for household plugs and socket-outlets. PC Electric GmbH has therefore tested the IK-codes of these products in accordance with IEC 62262 and according to the test method of IEC 60068-2-75 Ehc, with conditioning for 48 hours at 40°C and a relative humidity of 95%.

https://www.pcelectric.at/shop/en/?func=detail&artnr=253811-soc5

Changes and printing errors reserved!

8/13/2026