
article#	**8830gv**
article description	**Schutzkontakt-Unterputzsteckdose inkl. UP-Dose Design IP44 (grau)**
description long	Flush outlet with socket Design / DIN 49440 IP44 (grey) housing material: PC/ABS rated current: 16A number of poles: 3 (2P+PE) rated voltage/frequency: 250V~ / 50+60Hz contacts: brass nickel plated connection technology: screwless terminals color: grey (similar to RAL 7035) flush mounting (incl. Flush socket) hinged lid with inscription field (optional: key lock) IP protection class: IP44
GTIN (EAN)	9003399698736
country of origin	AT
customs number	85366990
net weight	0.264 kg
packaging quantitiy	6
minimum order quantitiy	6




ETIM 9.0	EC001321
Model	Flush-mounted
IEC-amperage	16 A
Number of poles	3
Voltage according to EN 60309-2	230 V (50+60 Hz) blue
Degree of protection (IP)	IP44
Connection system	Screw less terminal
Material	Plastic
Contact material	CuZn
Surface treatment contacts	Nickel-plated



a	90 mm
b	90 mm
c	92 mm
d	115 mm
e	64 mm
f	35 mm
wire flexible	1,5-2x2,5 mm²
wire solid	1,5-2x2,5 mm²
dismantling length	50 mm
stripping length	8-14 mm





https://www.pcelectric.at/shop/en/?func=detail&artnr=8830gv

Changes and printing errors reserved!