
article#	**6114-4k**
article description	**CEE-switched interlocked socket compact 16A 4p 4h IP44/IP54 knock-out**
description long	CEE-switched interlocked socket compact 16A 4p 4h IP44/IP54 knock-out housing material: PA6 + PC/ABS rated current: 16A number of poles: 4 (3P+PE) clock-position: 4h rated voltage/frequency: 100-130V~ / 50+60Hz contacts: brass nickel plated connection technology: screw terminals wall mounting housing with knock-out, mechanical interlock switch: ON/OFF PCE-Merz ML0; EN 60947-3; AC22A, 10kA IP protection class: IP44/IP54
country of origin	AT
customs number	85366990
packaging quantitiy	1
minimum order quantitiy	1



ETIM 9.0	EC001324
IEC-amperage	16 A
Number of poles	4
Voltage according to EN 60309-2	110 V (50+60 Hz) yellow
Clock hour position	4 h
Identification colour	Yellow
Degree of protection (IP)	IP54
Switch	Mechanical locking
Material housing	Plastic
Model	Base unit and cover
Contact material	CuZn
Surface treatment contacts	Nickel-plated



a	117 mm
wire flexible	1,5-2,5 mm²
wire solid	1,5-4 mm²
contact screws	120 Ncm
housing screws	110 Ncm
ambient temperature	-25 – 40 °C
temperature resistance	-25 – 80 °C

https://www.pcelectric.at/shop/en/?func=detail&artnr=6114-4k

Changes and printing errors reserved!

8/2/2023