| | |
|---|---|
| article# | **353568ER** |
| article description | **Ladesäule LS4 32A 3+3PH Z 22kW LAN ERK** |
| description long | LS4 charging pole for electric vehicles<br>in compliance with calibration law<br>Connection: 400V AC, 50Hz, 3-phase<br>Number of charging points: 2<br>Charging socket type 2 with locking device<br>Max. Power per charging point: 22kW<br>Charging current (max): 2 x 32A<br>Rated connected load: 44kW<br>Main switch over all outlets<br>Protection:<br>2 x RCCB type A + integr. DC fault current detection (6mA)<br>2 x MCB C 32A 4 poles<br>Authorisation: RFID<br>Controller: CC613 charge controller<br>Communication interface: LAN module with Ethernet router<br>Communication: OCPP 1.6 JSON, Modbus TCP<br>ISO 15118 Powerline Communication (PLC) for plug & charge / autocharge<br>meter in compliance with calibration law<br>WxDxH: 375x1400x208mm<br>material of housing: aluminium, anodised<br>mounting method: floor mounting<br>degree of protection: IP54<br>impact strength: IK10<br>Temperature control/heating: Yes<br>ambient temperature: -25°C to +40°C<br>Standards: acc. to EN 61851-1, IEC 61439-7<br>Branding: PCE standard, frontside<br>Backend system: no pre-configuration |
| GTIN (EAN) | 9003399592980 |
| country of origin | SE |
| customs number | 85371098 |
| net weight | 24.500 kg |
| minimum order quantitiy | 1 |

| | |
|---|---|
| ETIM 9.0 | EC002883 |
| Installation side connection model | 3-phase |
| Input voltage | 400 – 400 V |
| Frequency | 50 Hz |
| Nominal connection power | 44 kW |
| Number of charging units | 2 |
| Max. power per charging point | 22 kW |
| Width | 375 mm |
| Height | 1400 mm |
| Depth | 208 mm |
| Mounting method | Floor fastening |
| Number of socket outlets Type 2 | 2 |
| Number of earth leakage circuit breakers type A | 2 |
| Charging cable permanently lockable at charging device | True |
| DC residual current detection | True |
| With circuit breaker | True |
| Network-enabled as a master | True |
| Network-enabled as an extender | True |
| Networkable via LAN | True |
| Networkable via Wi-Fi | True |
| With built-in RFID card reader | True |
| NFC (Near Field Communication) | True |
| Suitable for dynamic load management | True |

| | |
|---|---|
| Open Charge Point Protocol (OCPP) version | 1.6 |
| Plug and charge (ISO 15118) | True |
| Material housing | Aluminium |
| Degree of protection (IP rating) | IP44 |
| Impact resistance (IK rating) | IK10 |






https://www.pcelectric.at/shop/en/?func=detail&artnr=353568ER

Changes and printing errors reserved!