
| | |
|---|---|
| article# | **12591-5v** |
| article description | **CEE-receptacle wall mount 30A 4P5W 5h IP44 UL** |
| description long | CEE-receptade wall mount 30A 4P5W 5h IP44 UL (PCE530RS5Sv)<br>housing material: PA6<br>rated current: 30A<br>number of poles: 4P5W (5p)<br>clock position: 5h<br>rated voltage: 347/600VAC<br>contacts: brass nickel plated<br>connection technology: screw terminals<br>IP protection class: IP44<br>according to UL1682<br>UL-product category: QLIW / QLIW7<br>UL-file number: E252008 |
| GTIN (EAN) | 9003399566172 |
| country of origin | AT |
| customs number | 85366990 |
| net weight | 0.292 kg |
| packaging quantitiy | 5 |
| minimum order quantitiy | 5 |



| | |
|---|---|
| ETIM 9.0 | EC001321 |
| Mounting method | Surface mounted |
| Amperage according to UL/CSA (for UL-version) | 30 A |
| Clock hour position | 5 h |
| Identification colour | Black |
| Degree of protection (IP) | IP44 |
| Connection system | Screwed terminal |
| Cable entry | Gland nut |
| Material | Plastic |
| Contact material | CuZn |
| Surface treatment contacts | Nickel-plated |
| Type of fastening | External mounting |




| | |
|---|---|
| a | 6.22 inch |
| b | 4.53 inch |
| wire flexible | 14-10 AWG |
| wire solid | 2,5-10 mm² |
| contact screws | 9.74 lbf-in |
| connecting screws | 9.74 lbf-in |
| dismantling length | 1.97 inch |
| stripping length | 0.47-0.55 inch |
| temperature resistance | -13 – 176 °F |

https://www.pcelectric.at/shop/en/?func=detail&artnr=12591-5v

Changes and printing errors reserved!

2/23/2026