

article#	**855-3v**
article description	**CEE-flanged socket Design 32A 5p 3h IP44 (white)**
description long	CEE-flanged socket Design 32A 5p 3h IP44 (white) housing material: PC/ABS rated current: 32A number of poles: 5 (3P+N+PE) clock-position: 3h rated voltage/frequency: 220/380V~ - 250/440V~ / 50/60Hz contacts: brass nickel plated connection technology: screw terminals color: white (similar to RAL 9016) for installation in cable trunking hinged lid with inscription field (optional: key lock) IP protection class: IP44
GTIN (EAN)	9003399640407
country of origin	AT
customs number	85366990
net weight	0.287 kg
packaging quantitiy	6
minimum order quantitiy	6





ETIM 9.0	EC001321
Model	Other
IEC-amperage	32 A
Number of poles	5
Voltage according to EN 60309-2	400-440 V (50+60 Hz) red
Clock hour position	3 h
Identification colour	Red
Degree of protection (IP)	IP44
Connection system	Screwed terminal
Material	Plastic
Contact material	CuZn
Surface treatment contacts	Nickel-plated



a	90 mm
b	90 mm
c	60 mm
d	60 mm
e	36 mm
f	48 mm
g	78 mm
gs	80 mm
h	74 mm
i	- mm
wire flexible	2,5-2x6 mm²
wire solid	2,5-2x10 mm²
contact screws	110 Ncm
dismantling length	50 mm
stripping length	12-14 mm
ambient temperature	-25 – 40 °C
temperature resistance	-25 – 80 °C

https://www.pcelectric.at/shop/en/?func=detail&artnr=855-3v

Changes and printing errors reserved!

9/27/2024