
article#	**0341-1**
article description	**CEE-plug 63A 4p 1h IP44 POWER TWIST**
description long	CEE-plug 63A 4p 1h IP44 POWER TWIST housing material: PA6 rated current: 63A number of poles: 4 (3P+PE) clock-position: 1h rated voltage/frequency: >50V / others contacts: brass nickel plated, with pilot pin connection technology: frame terminals with screws IP protection class: IP44
GTIN (EAN)	9003399553943
country of origin	AT
customs number	85366990
net weight	0.572 kg
packaging quantitiy	2
minimum order quantitiy	2



ETIM 10.0	EC000140
IEC-amperage	63 A
Number of poles	4
Voltage according to EN 60309-2	Other
Clock hour position	1 h
Identification colour	Grey
RAL-number	7046
Degree of protection (IP)	IP44
Connection system	Screwed terminal
Cable entry	Gland nut
Suitable for cable diameter	14.5 – 36 mm
Angle of plug	Straight
Material	Plastic
Contact material	CuZn
Surface treatment contacts	Nickel-plated



a	250 mm
b	102 mm
c	184 mm
K (cable Ø)	14,5-36 mm
SW	61 mm
wire flexible	6-16 mm²
contact screws	200 Ncm
connecting screws	200 Ncm
strain relief	1500 Ncm
dismantling length	100 mm
stripping length	15-18 mm
ambient temperature	-25 – 40 °C
temperature resistance	-25 – 80 °C

https://www.pcelectric.at/shop/en/?func=detail&artnr=0341-1

Changes and printing errors reserved!

3/18/2026