
article#	**525-4kd**
article description	**CEE-wall mounted plug 32A 5p 4h IP44 with lid**
description long	CEE-wall mounted plug 32A 5p 4h IP44 with lid housing material: PA6 rated current: 32A number of poles: 5 (3P+N+PE) clock-position: 4h rated voltage/frequency: 57/100V~ - 75/130V~ / 50+60Hz contacts: brass connection technology: screw terminals IP protection class: IP44
country of origin	AT
customs number	85366990
packaging quantitiy	5
minimum order quantitiy	5



ETIM 9.0	EC001319
IEC-amperage	32 A
Voltage according to EN 60309-2	110 V (50+60 Hz) yellow
Number of poles	5
Clock hour position	4 h
Identification colour	Yellow
Degree of protection (IP)	IP44
Connection system	Screwed terminal
Construction type	Surface mounted device plug
Phase inverter	False
Angle of plug	Angled
Material	Plastic
Contact material	CuZn
Surface treatment contacts	Untreated

a	151 mm
b	112 mm
wire flexible	2,5-6 mm²
wire solid	2,5-10 mm²
contact screws	110 Ncm
connecting screws	110 Ncm
dismantling length	50 mm
stripping length	12-14 mm
ambient temperature	-25 – 40 °C
temperature resistance	-25 – 80 °C



https://www.pcelectric.at/shop/en/?func=detail&artnr=525-4kd

Changes and printing errors reserved!

8/1/2023