
article#	**513-2**
article description	**CEE-wall mounted plug 16A 3p 2h IP44**
description long	CEE-wall mounted plug 16A 3p 2h IP44 housing material: PA6 rated current: 16A number of poles: 3 (2P+PE) clock-position: 2h rated voltage/frequency: >50V~ / 300-500Hz contacts: brass connection technology: screw terminals IP protection class: IP44
GTIN (EAN)	9003399057380
country of origin	AT
customs number	85366990
net weight	0.173 kg
packaging quantitiy	10
minimum order quantitiy	10



ETIM 9.0	EC001319
IEC-amperage	16 A
Voltage according to EN 60309-2	50-500 V (>300-500 Hz) green
Number of poles	3
Clock hour position	2 h
Identification colour	Green
Degree of protection (IP)	IP44
Connection system	Screwed terminal
Construction type	Surface mounted device plug
Phase inverter	False
Angle of plug	Angled
Material	Plastic
Contact material	CuZn
Surface treatment contacts	Untreated

a	120 mm
b	76 mm
wire flexible	1-2,5 mm²
wire solid	1-4 mm²
contact screws	100 Ncm
housing screws	110 Ncm
connecting screws	110 Ncm
dismantling length	50 mm
stripping length	10-12 mm
ambient temperature	-25 – 40 °C
temperature resistance	-25 – 80 °C



b=Höhe/height
Neigung/angle=15°

https://www.pcelectric.at/shop/en/?func=detail&artnr=513-2

Changes and printing errors reserved!

8/1/2023