
| | |
|---|---|
| article# | **60132-9** |
| article description | **CEE-switched interlocked socket compact 16A 3p 9h IP66/IP67** |
| description long | CEE-switched interlocked socket compact 16A 3p 9h IP66/IP67<br>housing material: PA6<br>rated current: 16A<br>number of poles: 3 (2P+PE)<br>clock-position: 9h<br>rated voltage/frequency: 380-415V~ / 50+60Hz<br>contacts: brass nickel plated<br>connection technology: screw terminals<br>panel mounting, mechanical interlock<br>switch: ON/OFF PCE-Merz ML0; EN 60947-3; AC22A, 10kA<br>IP protection class: IP66/IP67 |
| country of origin | AT |
| customs number | 85366990 |
| packaging quantitiy | 1 |
| minimum order quantitiy | 1 |




| | |
|---|---|
| ETIM 9.0 | EC001324 |
| IEC-amperage | 16 A |
| Number of poles | 3 |
| Voltage according to EN 60309-2 | 380-415 V (50+60 Hz) red |
| Clock hour position | 9 h |
| Identification colour | Red |
| Degree of protection (IP) | IP67 |
| Switch | Mechanical locking |
| Material housing | Plastic |
| Model | Top cover |
| Contact material | CuZn |
| Surface treatment contacts | Nickel-plated |

https://www.pcelectric.at/shop/en/?func=detail&artnr=60132-9

| | |
|---|---|
| a | 59 mm |
| wire flexible | 1,5-2,5 mm² |
| wire solid | 1,5-4 mm² |
| contact screws | 120 Ncm |
| ambient temperature | -25 – 40 °C |
| temperature resistance | -25 – 80 °C |



Changes and printing errors reserved!