OVE Austrian Electrotechnical Association
Eschenbachgasse 9 | 1010 Wien | Austria
ZVR: 327279890 | www.ove.at

OVE Certification
Kahlenberger Str. 2A | 1190 Wien | Austria
T +43 1 370 58 06 | certification@ove.at

Validity of ÖVE-Certificates can be checked at www.ove.at

ÖVE-CERTIFICATE

including the entitlement to use the Austrian Safety Mark

Certificate No.: **43-176-12**

Valid from: 2025 06 17
until: 2027 06 17

The Austrian Electrotechnical Association (OVE) hereby grants the right to the company mentioned below to label the listed products with the Austrian Safety Mark.

Certificate holder: **PC Electric Ges.m.b.H.**
Diesseits 145
4973 St. Martin im Innkreis
Austria

Product: **Switched socket-outlets for industrial purposes**

The products submitted by the applicant were type tested in accordance with the requirements of the technical standards and specifications listed in this certificate. OVE certifies the conformity of the listed products and those products manufactured strictly identical to the submitted ones (EN ISO/IEC 17067, Conformity Assessment Scheme Type 5).

The manufacturing process and the products are subject to ongoing surveillance based on harmonized European procedures. This certificate has been issued under the presumption and conditional on the fact that the certificate holder holds all necessary legal rights with regard to the product, presented for the testing and certification.

Results of testing are shown in file No(s).: **TGM-VA EE 39813**

Österreichischer Verband für Elektrotechnik
Head of OVE Certification
Digitally signed by M. Neugebauer
on behalf of T. Neumayer
Email=m.neugebauer@ove.at

Wien, 2025 08 07

Dipl.-Ing. T. Neumayer

Manufacturer:

PC Electric Ges.m.b.H.
Diesseits 145
4973 St. Martin im Innkreis
Austria

Factory location(s):

PC Electric Ges.m.b.H.
Diesseits 145
4973 St. Martin im Innkreis
Austria

PCE Polska Sp.z.o.o.
ul Podwalna 8A
58-200 Dzierzoniow
Poland

Tested and certified according to:

ÖVE/ÖNORM EN 60309-1:2013-03-01
ÖVE/ÖNORM EN 60309-2:2013-03-01
ÖVE/ÖNORM EN 60309-4:2012-12-01
OVE EN IEC 60309-1:2023-07-01
OVE EN IEC 60309-2:2023-07-01
OVE EN IEC 60309-4:2023-04-01
IEC 60309-1:2021
IEC 60309-2:2021
IEC 60309-4:2021

This certificate is the basis for the EU Declaration of Conformity and the CE Marking by the manufacturer or his agent and shows the conformity of the certified product(s) with the listed standards as defined by the **EU Low-Voltage Directive 2014/35/EU**. For the presumption of conformity according to Art. 12 with the safety objectives according to Art. 3 of the Directive, transitional periods given in the Official Journal of the European Union have to be observed.

Product: Switched socket-outlets for industrial purposes

Type designation: *Rating:*	***Trademark:***
960623.. Rated supply current: 32 A Rated insulation voltage: 690 V IP44 or IP44/IP54 with switch, alternatively additional with maximal 2 socket outlet of Type 1040 or 1050	PCE / ELCEE

960624.. PCE / ELCEE
Rated supply current: 32 A
Rated insulation voltage: 690 V
IP44 or IP44/IP54
with switch, alternatively additional with maximal
2 socket outlet of Type 1040 or 1050

960625.. PCE / ELCEE
Rated supply current: 32 A
Rated insulation voltage: 690 V
IP44 or IP44/IP54
with switch, alternatively additional with maximal
2 socket outlet of Type 1040 or 1050

960723.. PCE / ELCEE
Rated supply current: 32 A
Rated insulation voltage: 690 V
IP67 or IP66/IP67
with switch, alternatively additional with maximal
2 socket outlet of Type 2034 or 2035

960724.. PCE / ELCEE
Rated supply current: 32 A
Rated insulation voltage: 690 V
IP67 or IP66/IP67
with switch, alternatively additional with maximal
2 socket outlet of Type 2034 or 2035

960725.. PCE / ELCEE
Rated supply current: 32 A
Rated insulation voltage: 690 V
IP67 or IP66/IP67
with switch, alternatively additional with maximal
2 socket outlet of Type 2034 or 2035

Typecode

960 • 2 • • • • - • •

Special design
blank....standard design
*.....reserved for additonal versions (shutter, colour, etc.)

Clock position earthing contact
-1 .....1h
-3 .....3h
-4 .....4h
-5 .....5h
blank....6h
-7 .....7h
-9 .....9h
-11 .....11h
-12 .....12h

Switch
blank....ON/OFF Switch
1 .....reversing switch

Number of socket outlet for household
blank....without socket-outlet for household
1 .....one socket-outlet for household
2 .....two socket-outlet for household

optionally socket outlet for household
50 .....without socket-outlet for household
4 .....socket-outlet for household type 1040 (IP44), 2034* (IP67)
5 .....socket-outlet for household type 1050 (IP44), 2035* (IP67)
*.....reserved for additonal versions

Poles
3 .....socket-outlet type 423 (IP44), 4232 (IP67)
4 .....socket-outlet type 424 (IP44), 4242 (IP67)
5 .....socket-outlet type 425 (IP44), 4252 (IP67)

Rated current
2 .....32A

Degree of protection
6 .....IP44 or IP44/IP54
7 .....IP67 or IP66/IP67

Ground type
960 .....switched socket-outlet

Typelist

Type	Poles	Clock position earthing contact [h]	Rated operating voltage V [V]	Frequency [Hz]	Degree of protection [IP]
960623..	3	1	Other ratings	Other ratings	IP44 or IP44/IP54
		4	100 – 130	50 and 60	
		6*	200 – 250	50 and 60	
		7	480 – 500	50 and 60	
		9	380 – 415	50 and 60	
		12	Supply from an isolating transformer	50 and 60	
960624..	4	1	Other ratings	Other ratings	
		3	380 440	50 60	
		4	100 – 130	50 and 60	
		5	600 – 690	50 and 60	
		6*	380 – 415	50 and 60	
		7	480 – 500	50 and 60	
		9	200 – 250	50 and 60	
		11	440 – 460	60	
		12	Supply from an isolating transformer	50 and 60	
960625..	5	1	Other ratings	Other ratings	
		3	220/380 250/440	50 60	
		4	57/100 – 75/130	50 and 60	
		5	347/600 – 400/690	50 and 60	
		6*	200/346 – 240/415	50 and 60	
		7	277/480 – 288/500	50 and 60	
		9	120/208 – 144/250	50 and 60	
		11	250/440 – 265/460	60	
		12	Supply from an isolating transformer	50 and 60	

* Types with max 2 x socket outlet for household only available for clock position 6h.

Type	Poles	Clock position earthing contact [h]	Rated operating voltage V [V]	Frequency [Hz]	Degree of protection [IP]
960723..	3	1	Other ratings	Other ratings	IP67 or IP66/IP67
		4	100 – 130	50 and 60	
		6*	200 – 250	50 and 60	
		7	480 – 500	50 and 60	
		9	380 – 415	50 and 60	
		12	Supply from an isolating transformer	50 and 60	
960724..	4	1	Other ratings	Other ratings	
		3	380 440	50 60	
		4	100 – 130	50 and 60	
		5	600 – 690	50 and 60	
		6*	380 – 415	50 and 60	
		7	480 – 500	50 and 60	
		9	200 – 250	50 and 60	
		11	440 – 460	60	
		12	Supply from an isolating transformer	50 and 60	
960725..	5	1	Other ratings	Other ratings	
		3	220/380 250/440	50 60	
		4	57/100 – 75/130	50 and 60	
		5	347/600 – 400/690	50 and 60	
		6*	200/346 – 240/415	50 and 60	
		7	277/480 – 288/500	50 and 60	
		9	120/208 – 144/250	50 and 60	
		11	250/440 – 265/460	60	
		12	Supply from an isolating transformer	50 and 60	

* Types with max 2 x socket outlet for household only available for clock position 6h.