| | |
|---|---|
| article# | **9029074** |
| article description | **Distribution box plastic wall mounted SÖLDEN BV 63/5 32/5 2x16/5 3xSSD M40ÖoIP54** |
| description long | thermoplastic insulated distribution box - wall mounting series SOLDEN IP54 520x297x165 14TE<br>1x thrilling hole M40 on top, 1x blind cable gland M40 from bottom<br>1xCEE-socket 63A 5p 400V protected with prefuse of supply line<br>1xCEE-socket 32A 5p 400V protected with 1xMCB 32A 3p C<br>2xCEE-socket 16A 5p 400V protected with 1xMCB 16A 3p C<br>3x socket DIN49440 16A 250V IP54 protected with 3xMCB 16A 1p C<br>1xRCD 63A/4/0.03A (TYP A 63AT) over all outlets MCB and RCD made by Eaton ÖVE / VDE distribution box is wired on terminals up to max.5x25qmm (5x16qmm flexible wire!) |
| GTIN (EAN) | 9003399295256 |
| country of origin | AT |
| customs number | 85371098 |
| net weight | 8.000 kg |
| packaging quantitiy | 1 |
| minimum order quantitiy | 1 |



https://www.pcelectric.at/shop/en/?func=detail&artnr=9029074

| | |
|---|---|
| ETIM 9.0 | EC000379 |
| CEE socket outlet 16 A | 2x16A5p400V |
| CEE socket outlet 32 A | 1x32A5p400V |
| CEE socket outlet 63 A | 1x63A5p400V |
| Number of socket outlets with protective contact CEE 7/3 (type F) | 3 |
| Protection | Overcurrent switch |
| Earth leakage switch | Earth leakage switch with IFN 30 mA (standard) |
| Number of miniature circuit breakers | 5 |
| Material housing | Plastic |
| Power supply/connection possibility | 1 cable (branch line) |
| Handling | Wall mounting |
| Degree of protection (IP) | IP54 |
| Colour | Grey |
| Height | 520 mm |
| Width | 297 mm |
| Depth | 165 mm |

Changes and printing errors reserved!