
article#	**9755098**
article description	**CEE-switched interlocked socket 125A 4p 7h IP67**
description long	CEE-switched interlocked socket 125A 4p 7h IP67 housing material: PC/ABS rated current: 125A number of poles: 4 (3P+PE) clock-position: 7h rated voltage/frequency: 480-500V~ / 50+60Hz contacts: brass, with lamellar spring (CuBe) connection technology: screw terminals wall mounting, mechanical interlock switch: ON/OFF PCE-Merz ML3; EN 60947-3; AC22A (AC3, 690V, 3~, 45kW) cable entry: top IP protection class: IP67
GTIN (EAN)	9003399001468
country of origin	AT
customs number	85366990
net weight	4.700 kg
packaging quantitiy	1
minimum order quantitiy	1



https://www.pcelectric.at/shop/en/?func=detail&artnr=9755098

ETIM 9.0	EC001324
IEC-amperage	125 A
Number of poles	4
Voltage according to EN 60309-2	500 V (50+60 Hz) black
Clock hour position	7 h
Identification colour	Black
Degree of protection (IP)	IP67
Switch	Mechanical locking
Material housing	Plastic
Model	Base unit and cover
Contact material	CuZn
Surface treatment contacts	Untreated

wire flexible	16-50 mm²
wire solid	16-70 mm²
ambient temperature	-25 – 40 °C
temperature resistance	-25 – 80 °C



Changes and printing errors reserved!

2/26/2026