
| | |
|---|---|
| article# | **01492-12v** |
| article description | **CEE-plug 20A 3P4W 12h IP67 UL** |
| description long | CEE-plug 20A 3P4W 12h IP67 UL<br>(PCE420P12Wv)<br>housing material: PA6<br>rated current: 20A<br>number of poles: 3P4W (4p)<br>clock position: 12h<br>rated voltage: 120/250VAC single phase<br>contacts: brass nickel plated<br>connection technology: screw terminals<br>IP protection class: IP67<br>according to UL1682<br>UL-product category: QLHN / QLHN7<br>UL-file number: E232901 |
| country of origin | AT |
| customs number | 85366990 |
| packaging quantitiy | 10 |
| minimum order quantitiy | 10 |



| | |
|---|---|
| ETIM 10.0 | EC000140 |
| Amperage according to UL/CSA (for UL-version) | 20 A |
| Number of poles | 4 |
| Clock hour position | 12 h |
| Degree of protection (IP) | IP67 |
| Connection system | Screwed terminal |
| Cable entry | Gland nut |
| Suitable for cable diameter | 9 – 15 mm |
| Angle of plug | Straight |
| Material | Plastic |
| Contact material | CuZn |
| Surface treatment contacts | Nickel-plated |




| | |
|---|---|
| a | 5.04 inch |
| b | 3.11 inch |
| K (cable Ø) | 0.35-0.59 inch |
| SW | 1.65 inch |
| wire flexible | 16-12 AWG |
| contact screws | 8.85 lbf-in |
| strain relief | 44.3 lbf-in |
| dismantling length | 1.97 inch |
| stripping length | 0.39-0.47 inch |
| temperature resistance | -13 – 176 °F |

https://www.pcelectric.at/shop/en/?func=detail&artnr=01492-12v

Changes and printing errors reserved!

3/18/2026