article#	**353410P**
article description	**Wallbox GLB 22KW, charging socket Type2 + RCD A**
description long	Wallbox GLB - charging station for electric vehicles Connection: (230)400V AC, 50Hz, (single)3-phase Number of charging units: 1 Socket Outlet Type 2 with locking actuator Max. power per charging point: 22kW Charging current (min-max): 6A - 32A Nominal connection power: 22kW Protection: RCCB Type A, DC-fault protection (6mA) Access control: input for external key switch,... Material housing: Plastic/ black Lockable cover WxHxD: 205x422x124 mm Mounting method: Wall mounting Degree of protection: IP44 Impact strength: IK08 Ambient temperature: -25°C bis +40°C Standards: acc. EN 61851-1, IEC 61439-7 Adjustable charging current: 6A, 10A, 13A, 16A, 20A, 25A, 32A
GTIN (EAN)	7331185186887
country of origin	PL
customs number	85371098
net weight	3.770 kg
packaging quantitiy	0
minimum order quantitiy	1









https://www.pcelectric.at/shop/en/?func=detail&artnr=353410P

ETIM 9.0	EC002883
Installation side connection model	3-phase
Input voltage	230 – 400 V
Frequency	50 Hz
Nominal connection power	22 kW
Number of charging units	1
Max. power per charging point	22 kW
Width	205 mm
Height	422 mm
Depth	124 mm
Mounting method	Wall mounting
Number of socket outlets Type 2	1
Number of earth leakage circuit breakers type A	1
Charging cable permanently lockable at charging device	True
DC residual current detection	True
Contactor welding detection	False
With circuit breaker	False
Network-enabled as a master	True
Network-enabled as an extender	True
Networkable via LAN	True
Networkable via Wi-Fi	False
LTE	False
With energy meter	False
With built-in RFID card reader	False
NFC (Near Field Communication)	False
Static load management integrated	True
Suitable for dynamic load management	True

Changes and printing errors reserved!

5/7/2024