
| | |
|---|---|
| article# | **0351-5** |
| article description | **CEE-plug 63A 5p 5h IP44 POWER TWIST** |
| description long | CEE-plug 63A 5p 5h IP44 POWER TWIST<br>housing material: PA6<br>rated current: 63A<br>number of poles: 5 (3P+N+PE)<br>clock-position: 5h<br>rated voltage/frequency: 347/600V~ - 400/690V~ / 50+60Hz<br>contacts: brass nickel plated, with pilot pin<br>connection technology: frame terminals with screws<br>IP protection class: IP44 |
| GTIN (EAN) | 9003399931420 |
| country of origin | AT |
| customs number | 85366990 |
| net weight | 0.621 kg |
| packaging quantitiy | 2 |
| minimum order quantitiy | 2 |



| | |
|---|---|
| ETIM 10.0 | EC000140 |
| IEC-amperage | 63 A |
| Number of poles | 5 |
| Voltage according to EN 60309-2 | 600-690 V (50+60 Hz) black |
| Clock hour position | 5 h |
| Identification colour | Black |
| RAL-number | 7046 |
| Degree of protection (IP) | IP44 |
| Connection system | Screwed terminal |
| Cable entry | Gland nut |
| Suitable for cable diameter | 14.5 – 36 mm |
| Angle of plug | Straight |
| Material | Plastic |
| Contact material | CuZn |
| Surface treatment contacts | Nickel-plated |




| | |
|---|---|
| a | 250 mm |
| b | 102 mm |
| c | 184 mm |
| K (cable Ø) | 14,5-36 mm |
| SW | 61 mm |
| wire flexible | 6-16 mm² |
| contact screws | 200 Ncm |
| connecting screws | 200 Ncm |
| strain relief | 1500 Ncm |
| dismantling length | 100 mm |
| stripping length | 15-18 mm |
| ambient temperature | -25 – 40 °C |
| temperature resistance | -25 – 80 °C |

https://www.pcelectric.at/shop/en/?func=detail&artnr=0351-5

3/18/2026 Changes and printing errors reserved!