
article#	**75133-4**
article description	**CEE-wall mounted socket mit Fenster 16A 3p 4h IP44**
description long	CEE-wall mounted socket with window 16A 3p 4h IP44 housing material: PC/ABS rated current: 16A number of poles: 3 (2P+PE) clock-position: 4h rated voltage/frequency: 100-130V~ / 50+60Hz contacts: brass nickel plated connection technology: screw terminals cable entry: top, bottom, rear inc. threaded blind cap with hinged window (5 modules) and DIN rail IP protection class: IP44
GTIN (EAN)	9003399099342
country of origin	AT
customs number	85366990
net weight	0.917 kg
packaging quantitiy	1
minimum order quantitiy	1



ETIM 9.0	EC000379
CEE socket outlet 16 A	1x16A xp xxxV
Other fixtures and/or empty locations	5
Material housing	Plastic
Contact material	CuZn
Surface treatment contacts	Nickel-plated
Handling	Wall mounting
Degree of protection (IP)	IP54
Colour	Grey



a	249 mm
b	141 mm
wire flexible	1-2,5 mm²
wire solid	1-4 mm²
contact screws	100 Ncm
housing screws	110 Ncm
dismantling length	50 mm
stripping length	10-12 mm
ambient temperature	-25 – 40 °C
temperature resistance	-25 – 80 °C

https://www.pcelectric.at/shop/en/?func=detail&artnr=75133-4

Changes and printing errors reserved!

9/25/2023