
article#	**52592-7k**
article description	**CEE-inlet wall mount 30A 4P5W 7h IP67 UL**
description long	CEE-inlet wall mount 30A 4P5W 7h IP67 UL (PCE530BS7W) housing material: PA6 rated current: 30A number of poles: 4P5W (5p) clock position: 7h rated voltage: 277/480VAC contacts: brass connection technology: screw terminals IP protection class: IP67 according to UL1682 UL-product category: QLIW / QLIW7 UL-file number: E252008
GTIN (EAN)	9003399544897
country of origin	AT
customs number	85366990
net weight	0.306 kg
packaging quantitiy	5
minimum order quantitiy	5



ETIM 9.0	EC001319
Amperage according to UL/CSA (for UL-version)	30 A
Number of poles	5
Clock hour position	7 h
Identification colour	Red
Degree of protection (IP)	IP67
Connection system	Screwed terminal
Construction type	Surface mounted device plug
Angle of plug	Angled
Material	Plastic
Contact material	CuZn
Surface treatment contacts	Untreated



a	5.98 inch
b	4.02 inch
c	4.02 inch
wire flexible	14-10 AWG
wire solid	2,5-10 mm²
contact screws	9.74 lbf-in
connecting screws	9.74 lbf-in
dismantling length	1.97 inch
stripping length	0.47-0.55 inch
temperature resistance	-13 – 176 °F

https://www.pcelectric.at/shop/en/?func=detail&artnr=52592-7k

Changes and printing errors reserved!

2/23/2026