
article#	**02592-7v**
article description	**CEE-plug 30A 4P5W 7h IP67 UL**
description long	CEE-plug 30A 4P5W 7h IP67 UL (PCE530P7Wv) housing material: PA6 rated current: 30A number of poles: 4P5W (5p) clock position: 7h rated voltage: 277/480VAC contacts: brass nickel plated connection technology: screw terminals IP protection class: IP67 according to UL1682 UL-product category: QLHN / QLHN7 UL-file number: E232901
GTIN (EAN)	9003399926839
country of origin	AT
customs number	85366990
net weight	0.276 kg
packaging quantitiy	10
minimum order quantitiy	10



ETIM 10.0	EC000140
Amperage according to UL/CSA (for UL-version)	30 A
Number of poles	5
Clock hour position	7 h
Identification colour	Red
Degree of protection (IP)	IP67
Connection system	Screwed terminal
Cable entry	Gland nut
Suitable for cable diameter	13.3 – 19.3 mm
Angle of plug	Straight
Material	Plastic
Contact material	CuZn
Surface treatment contacts	Nickel-plated



a	6.10 inch
b	3.94 inch
K (cable Ø)	0.52-0.76 inch
SW	1.97 inch
wire flexible	14-10 AWG
contact screws	9.74 lbf-in
strain relief	62.0 lbf-in
dismantling length	1.97 inch
stripping length	0.47-0.55 inch
temperature resistance	-13 – 176 °F

https://www.pcelectric.at/shop/en/?func=detail&artnr=02592-7v

Changes and printing errors reserved!

3/18/2026