
article#	**2522-gs**
article description	**Taurus2 solid rubber safety connector lid nat IP54 (light grey/black)**
description long	Safety connector series Taurus2 - solid rubber with hinged lid color (housing/ring/cover): light grey/black/black material (housing/contact carrier): TPE/TPE earthing system: Austrian/German 16A/ 250V AC / 3p (2P+E), protection rating: IP54
GTIN (EAN)	9003399472824
country of origin	AT
customs number	85366990
net weight	0.098 kg
packaging quantitiy	20
minimum order quantitiy	500





ETIM 10.0	EC001327
Model	Coupler with protective contact CEE 7/3 (type F)
Material	Rubber
Material quality	Solid rubber
Degree of protection (IP)	IP54
Insert direction	Straight
Connection system	Screwed terminal
Colour	Grey
Number of poles	3
Nominal voltage	250 V
Nominal current	16 A
For heavy conditions according to VDE	True

https://www.pcelectric.at/shop/en/?func=detail&artnr=2522-gs

K (cable Ø)	6-13 mm
wire flexible	1-2,5 mm²
contact screws	80 Ncm
housing screws	110 Ncm
strain relief	110 Ncm
dismantling length	30 mm
stripping length	7 mm
ambient temperature	-25 – 40 °C



Changes and printing errors reserved!

3/19/2026