
article#	**12491-7v**
article description	**CEE-receptacle wall mount 30A 3P4W 7h IP44 UL**
description long	CEE-receptade wall mount 30A 3P4W 7h IP44 UL (PCE430RS7Sv) housing material: PA6 rated current: 30A number of poles: 3P4W (4p) clock position: 7h rated voltage: 480VAC contacts: brass nickel plated connection technology: screw terminals IP protection class: IP44 according to UL1682 UL-product category: QLIW / QLIW7 UL-file number: E252008
GTIN (EAN)	9003399552939
country of origin	AT
customs number	85366990
net weight	0.265 kg
packaging quantitiy	5
minimum order quantitiy	5



ETIM 9.0	EC001321
Mounting method	Surface mounted
Amperage according to UL/CSA (for UL-version)	30 A
Clock hour position	7 h
Identification colour	Red
Degree of protection (IP)	IP44
Connection system	Screwed terminal
Cable entry	Gland nut
Material	Plastic
Contact material	CuZn
Surface treatment contacts	Nickel-plated
Type of fastening	External mounting



a	6.18 inch
b	4.37 inch
wire flexible	14-10 AWG
wire solid	2,5-10 mm²
contact screws	9.74 lbf-in
connecting screws	9.74 lbf-in
dismantling length	1.97 inch
stripping length	0.47-0.55 inch
temperature resistance	-13 – 176 °F

https://www.pcelectric.at/shop/en/?func=detail&artnr=12491-7v

Changes and printing errors reserved!

2/23/2026