
| | |
|---|---|
| article# | **513-6ttv** |
| article description | **CEE-wall mounted plug 16A 3p 6h IP44 TT** |
| description long | CEE-wall mounted plug 16A 3p 6h IP44 TT<br>housing material: PA6<br>rated current: 16A<br>number of poles: 3 (2P+PE)<br>clock-position: 6h<br>rated voltage/frequency: 200-250V~ / 50+60Hz<br>contacts: brass nickel plated<br>connection technology: screwless terminals (TT)<br>IP protection class: IP44 |
| country of origin | AT |
| customs number | 85366990 |
| packaging quantitiy | 10 |
| minimum order quantitiy | 10 |



| | |
|---|---|
| ETIM 9.0 | EC001319 |
| IEC-amperage | 16 A |
| Voltage according to EN 60309-2 | 230 V (50+60 Hz) blue |
| Number of poles | 3 |
| Clock hour position | 6 h |
| Identification colour | Blue |
| Degree of protection (IP) | IP44 |
| Connection system | Screw less terminal |
| Construction type | Surface mounted device plug |
| Phase inverter | False |
| Angle of plug | Angled |
| Material | Plastic |
| Contact material | CuZn |
| Surface treatment contacts | Nickel-plated |




b=Höhe/height
Neigung/angle=15°

| | |
|---|---|
| a | 120 mm |
| b | 76 mm |
| wire flexible | 1-2,5 mm² |
| wire solid | 1-4 mm² |
| housing screws | 110 Ncm |
| connecting screws | 110 Ncm |
| dismantling length | 50 mm |
| stripping length | 10-12 mm |
| ambient temperature | -25 – 40 °C |
| temperature resistance | -25 – 80 °C |

https://www.pce-electric.at/shop/en/?func=detail&artnr=513-6ttv

Changes and printing errors reserved!

8/1/2023