
article#	**0239-6**
article description	**CEE-plug 30A 2P3W 6h IP44 UL**
description long	CEE-plug 30A 2P3W 6h IP44 UL (PCE330P6S) housing material: PA6 rated current: 32A/30A number of poles: 2P3W (3p) clock position: 6h rated voltage: 250VAC contacts: brass connection technology: screw terminals IP protection class: IP44 according to UL1682 und IEC/EN 60309-2 (SERIE II) UL-product category: QLHN / QLHN7 UL-file number: E232901
GTIN (EAN)	9003399075148
country of origin	AT
customs number	85366990
net weight	0.181 kg
packaging quantitiy	10
minimum order quantitiy	10



ETIM 10.0	EC000140
IEC-amperage	32 A
Amperage according to UL/CSA (for UL-version)	30 A
Number of poles	3
Clock hour position	6 h
Identification colour	Blue
Degree of protection (IP)	IP44
Connection system	Screwed terminal
Cable entry	Gland nut
Suitable for cable diameter	13.3 – 19.3 mm
Angle of plug	Straight
Material	Plastic
Contact material	CuZn
Surface treatment contacts	Untreated



a	5.91 inch
b	4.09 inch
c	2.48 inch
K (cable Ø)	0.52-0.76 inch
SW	1.97 inch
wire flexible	14-10 AWG
contact screws	9.74 lbf-in
strain relief	62.0 lbf-in
dismantling length	1.97 inch
stripping length	0.47-0.55 inch
temperature resistance	-13 – 176 °F

https://www.pcelectric.at/shop/en/?func=detail&artnr=0239-6

Changes and printing errors reserved!

3/18/2026