
article#	**5139-6**
article description	**CEE-inlet wall mount 20A 2P3W 6h IP44 UL**
description long	CEE-inlet wall mount 20A 2P3W 6h IP44 UL (PCE320BS6S) housing material: PA6 rated current: 16A/20A number of poles: 2P3W (3p) clock position: 6h rated voltage: 250VAC contacts: brass connection technology: screw terminals IP protection class: IP44 according to UL1682 und IEC/EN 60309-2 (SERIE II) UL-product category: QLIW / QLIW7 UL-file number: E252008
GTIN (EAN)	9003399538070
country of origin	AT
customs number	85366990
net weight	0.173 kg
packaging quantitiy	10
minimum order quantitiy	10



ETIM 9.0	EC001319
IEC-amperage	16 A
Amperage according to UL/CSA (for UL-version)	20 A
Number of poles	3
Clock hour position	6 h
Identification colour	Blue
Degree of protection (IP)	IP44
Connection system	Screwed terminal
Construction type	Surface mounted device plug
Angle of plug	Angled
Material	Plastic
Contact material	CuZn
Surface treatment contacts	Untreated



a	4.72 inch
b	2.99 inch
wire flexible	16-12 AWG
wire solid	1-4 mm²
contact screws	8.85 lbf-in
housing screws	9.74 lbf-in
connecting screws	9.74 lbf-in
dismantling length	1.97 inch
stripping length	0.39-0.47 inch
temperature resistance	-13 – 176 °F

https://www.pcelectric.at/shop/en/?func=detail&artnr=5139-6

Changes and printing errors reserved!

2/23/2026