
article#	**05721-shu**
article description	**Safety plug 2SL IP54 green series TopTaurus2**
description long	Safety plug series TopTaurus2 color: black-green, material: PA6 2-component rubberized screwless quick lock system for housing cover and strain relief earthing system: dual earthing system 16A/ 250V AC / 3p (2P+E), protection rating: IP54
GTIN (EAN)	9003399491863
country of origin	AT
customs number	85366990
net weight	0.100 kg
packaging quantitiy	20
minimum order quantitiy	200



ETIM 10.0	EC000242
Model	Hybrid plug CEE 7/7 (type E/F)
Protective contact	Earthing clips
Material	Plastic
Material quality	Thermoplastic
Degree of protection (IP)	IP54
Insert direction	Straight
Connection system	Screwed terminal
Colour	Green
Number of poles	3
Nominal voltage	250 V
Nominal current	16 A
For heavy conditions according to VDE	True



K (cable Ø)	6-14 mm
SW	21 mm
wire flexible	0,75-2,5 mm²
contact screws	80 Ncm
strain relief	400 Ncm
dismantling length	30 mm
stripping length	7 mm
ambient temperature	-25 – 40 °C
IK-code *)	IK10



*) The IK-test is not part of the IEC 60309 standard for industrial plugs and socket-outlets or the IEC 60884 standard for household plugs and socket-outlets. PC Electric GmbH has therefore tested the IK-codes of these products in accordance with IEC 62262 and according to the test method of IEC 60068-2-75 Ehc, with conditioning for 48 hours at 40°C and a relative humidity of 95%.

https://www.pcelectric.at/shop/en/?func=detail&artnr=05721-shu

Changes and printing errors reserved!

3/19/2026