article#	**9545069**
article description	**Distribution box rubber mobile Zirl BV 2x63/5 2x32/5 2x16/5 5xSSD2m5G35**
description long	solid rubber distribution box model ZIRL IP54 527x400x270(HxBxT) universal with 2x handle on top and 2x adjustable feet from bottom (stackable) 2m cable H07RN-F 5G35 black with CEE-plug 125A 5p 400V 6h 2xCEE-sockets 63A 5p 400V IP67 fused with 2xMCB`s 63A 3p C (before FI) 2xCEE-sockets 32A 5p 400V fused with 2xMCB`s 32A 3p C (before FI) 2xCEE-sockets 16A 5p 400V fused with 2xMCB`s 16A 3p C 5xSK-sockets 16A 250V IP54 fused with 5xMCB`s 16A 1p C 2xRCD 63A/4/0.03A (TYP A 63AT) over 2xCEE 63/5 outlets 2xRCD 40A/4/0.03A (TYP A 40AT) over 2xCEE 32/5 outlets 1xRCD 63A/4/0.03A (TYP A 63AT) over 2xCEE 16/5 and 6xSK-sockets pre-fused with 1xMCB 63A 3p C MCB`s and RCD`s are SIEMENS brandes distribution box is ready wired for using
GTIN (EAN)	9003399848896
country of origin	AT
customs number	85371098
net weight	40.000 kg
packaging quantitiy	1
minimum order quantitiy	1





https://www.pcelectric.at/shop/en/?func=detail&artnr=9545069

ETIM 9.0	EC000379
CEE socket outlet 16 A	2x16A5p400V
CEE socket outlet 32 A	2x32A5p400V
CEE socket outlet 63 A	2x63A5p400V
Number of socket outlets with protective contact CEE 7/3 (type F)	5
Protection	Overcurrent switch
Earth leakage switch	Earth leakage switch with IFN 30 mA (standard)
Number of miniature circuit breakers	11
Material housing	Rubber
Power supply/connection possibility	Feeder cable with plug
Type of mains connection	CEE 125 A
Cable length	2 m
Handling	Portable
Degree of protection (IP)	IP54
Colour	Black
Height	527 mm
Width	400 mm
Depth	270 mm

Changes and printing errors reserved!