
| | |
|---|---|
| article# | **524-2** |
| article description | **CEE-wall mounted plug 32A 4p 2h IP44** |
| description long | CEE-wall mounted plug 32A 4p 2h IP44<br>housing material: PA6<br>rated current: 32A<br>number of poles: 4 (3P+PE)<br>clock-position: 2h<br>rated voltage/frequency: >50V~ / 300-500Hz<br>contacts: brass<br>connection technology: screw terminals<br>IP protection class: IP44 |
| GTIN (EAN) | 9003399540448 |
| country of origin | AT |
| customs number | 85366990 |
| net weight | 0.232 kg |
| packaging quantitiy | 10 |
| minimum order quantitiy | 10 |




| | |
|---|---|
| ETIM 9.0 | EC001319 |
| IEC-amperage | 32 A |
| Voltage according to EN 60309-2 | 50-500 V (>300-500 Hz) green |
| Number of poles | 4 |
| Clock hour position | 2 h |
| Identification colour | Green |
| Degree of protection (IP) | IP44 |
| Connection system | Screwed terminal |
| Construction type | Surface mounted device plug |
| Phase inverter | False |
| Angle of plug | Angled |
| Material | Plastic |
| Contact material | CuZn |
| Surface treatment contacts | Untreated |




b=Höhe/height
Neigung/angle=15°

| | |
|---|---|
| a | 131 mm |
| b | 82 mm |
| wire flexible | 2,5-6 mm² |
| wire solid | 2,5-10 mm² |
| contact screws | 110 Ncm |
| housing screws | 110 Ncm |
| connecting screws | 110 Ncm |
| dismantling length | 50 mm |
| stripping length | 12-14 mm |
| ambient temperature | -25 – 40 °C |
| temperature resistance | -25 – 80 °C |

https://www.pcelectric.at/shop/en/?func=detail&artnr=524-2

Changes and printing errors reserved!

8/1/2023