
| | |
|---|---|
| article# | **12391-5** |
| article description | **CEE-receptacle wall mount 30A 2P3W 5h IP44 UL** |
| description long | CEE-receptade wall mount 30A 2P3W 5h IP44 UL (PCE330RS5S)<br>housing material: PA6<br>rated current: 30A<br>number of poles: 2P3W (3p)<br>clock position: 5h<br>rated voltage: 277VAC<br>contacts: brass<br>connection technology: screw terminals<br>IP protection class: IP44<br>according to UL1682<br>UL-product category: QLIW / QLIW7<br>UL-file number: E252008 |
| country of origin | AT |
| customs number | 85366990 |
| packaging quantitiy | 5 |
| minimum order quantitiy | 5 |



| | |
|---|---|
| ETIM 9.0 | EC001321 |
| Mounting method | Surface mounted |
| Amperage according to UL/CSA (for UL-version) | 30 A |
| Clock hour position | 5 h |
| Identification colour | Grey |
| Degree of protection (IP) | IP44 |
| Connection system | Screwed terminal |
| Cable entry | Gland nut |
| Material | Plastic |
| Contact material | CuZn |
| Surface treatment contacts | Untreated |
| Type of fastening | External mounting |




| | |
|---|---|
| a | 6.18 inch |
| b | 4.37 inch |
| wire flexible | 14-10 AWG |
| wire solid | 2,5-10 mm² |
| contact screws | 9.74 lbf-in |
| connecting screws | 9.74 lbf-in |
| dismantling length | 1.97 inch |
| stripping length | 0.47-0.55 inch |
| temperature resistance | -13 – 176 °F |

https://www.pcelectric.at/shop/en/?func=detail&artnr=12391-5

Changes and printing errors reserved!

2/23/2026