
| | |
|---|---|
| article# | **2272-7v** |
| article description | **CEE-connector 32A 7p 7h IP66/IP67 SHARK** |
| description long | CEE-connector 32A 7p 7h IP66/IP67 SHARK<br>housing material: PA6<br>rated current: 32A<br>number of poles: 7 (6P+PE)<br>clock-position: 7h<br>rated voltage/frequency: 480-500V~ / 50+60Hz<br>contacts: brass nickel plated<br>connection technology: screw terminals<br>IP protection class: IP66/IP67 |
| GTIN (EAN) | 9003399310201 |
| country of origin | AT |
| customs number | 85366990 |
| net weight | 0.377 kg |
| packaging quantitiy | 10 |
| minimum order quantitiy | 10 |



| | |
|---|---|
| ETIM 9.0 | EC001320 |
| IEC-amperage | 32 A |
| Number of poles | 7 |
| Voltage according to EN 60309-2 | 500 V (50+60 Hz) black |
| Clock hour position | 7 h |
| Identification colour | Black |
| Degree of protection (IP) | IP67 |
| Connection system | Screwed terminal |
| Angle of plug | Straight |
| Cable entry | Gland nut |
| Material | Plastic |
| Contact material | CuZn |
| Surface treatment contacts | Nickel-plated |




| | |
|---|---|
| a | 171 mm |
| b | 102 mm |
| K (cable Ø) | 11,5-22 mm |
| SW | 50 mm |
| wire flexible | 2,5-6 mm² |
| contact screws | 110 Ncm |
| strain relief | 600 Ncm |
| dismantling length | 50 mm |
| stripping length | 12-14 mm |
| ambient temperature | -25 – 40 °C |
| temperature resistance | -25 – 80 °C |

https://www.pcelectric.at/shop/en/?func=detail&artnr=2272-7v

Changes and printing errors reserved!

8/1/2023