#### **OVE Austrian Electrotechnical Association**

Eschenbachgasse 9 | 1010 Wien | Austria ZVR: 327279890 | www.ove.at

OVE Certification

Kahlenberger Str. 2A | 1190 Wien | Austria T +43 1 370 58 06 | certification@ove.at

Validity of ÖVE-Certificates can be checked at www.ove.at



Page 1 of 5

# **ÖVE-CERTIFICATE**

including the entitlement to use the Austrian Safety Mark



Certificate No.: 43-163-14 Valid from: 2023 04 19

until: 2025 04 19

The Austrian Electrotechnical Association (OVE) hereby grants the right to the company mentioned below to label the listed products with the Austrian Safety Mark.

Company: PC Electric Ges.m.b.H.

Diesseits 145

4973 St. Martin im Innkreis

Austria

Product: Switched socket-outlets for industrial purpose

The products submitted by the applicant were type tested in accordance with the requirements of the technical standards and specifications listed in this certificate. OVE certifies the conformity of the listed products and those products manufactured strictly identical to the submitted ones (EN ISO/IEC 17067, Conformity Assessment Scheme Type 5).

The manufacturing process and the products are subject to ongoing surveillance based on harmonized European procedures. This certificate has been issued under the presumption and conditional on the fact that the applicant holds all necessary legal rights with regard to the product, presented for the testing and certification.

Results of testing are shown in file No(s):: 3704-1858/22

Österreichischer Verband für Elektrotechnik

Head of OVE Certification


Digitally signed by T. Neumayer Email=t neumayer@ove.at

Dipl.-Ing. T. Neumayer

OVE

Wien, 2023 03 06

**OVE Certification** 







Date: 2023 03 06 Page 2 of 5

#### Manufacturer:

PC Electric Ges.m.b.H. Diesseits 145 4973 St. Martin im Innkreis Austria

#### Factory location(s):

PC Electric Ges.m.b.H. Diesseits 145 4973 St. Martin im Innkreis Austria

### Tested and certified according to:

ÖVE/ÖNORM EN 60309-1:2013-03-01 ÖVE/ÖNORM EN 60309-2:2013-03-01 ÖVE/ÖNORM EN 60309-4:2012-12-01 EN IEC 60309-1:2022 EN IEC 60309-2:2022 EN IEC 60309-4:2022 IEC 60309-1:2021 IEC 60309-4:2021 IEC 60309-4:2021

This certificate is the basis for the EU Declaration of Conformity and the CE Marking by the manufacturer or his agent and shows the conformity of the certified product(s) with the listed standards as defined by the **EU Low-Voltage Directive 2014/35/EU**. For the presumption of conformity according to Art. 12 with the safety objectives according to Art. 3 of the Directive, transitional periods given in the Official Journal of the European Union have to be observed.

## **Product: Switched socket-outlets for industrial purpose**

 Type designation:
 Trademark:

 Rating:
 PCE / ELCEE / IDE

 6023
 PCE / ELCEE / IDE

 Rated current: 32 A
 PCE / ELCEE / IDE

 6123
 PCE / ELCEE / IDE

 Rated current: 32 A
 IP44 or IP44/IP54

 2P+PE
 PCE / ELCEE / IDE







Date: 2023 03 06

Page 3 of 5

6024 PCE / ELCEE / IDE

Rated current: 32 A IP44 or IP44/IP54

3P+PE

6124 PCE / ELCEE / IDE

Rated current: 32 A IP44 or IP44/IP54

3P+PE

6025 PCE / ELCEE / IDE

Rated current: 32 A IP44 or IP44/IP54

3P+N+PE

PCE / ELCEE / IDE

Rated current: 32 A IP44 or IP44/IP54 3P+N+PE

-- -- -

60232 PCE / ELCEE / IDE

Rated current: 32 A IP67 or IP66/IP67

2P+PE

61232 PCE / ELCEE / IDE

Rated current: 32 A IP67 or IP66/IP67

2P+PE

60242 PCE / ELCEE / IDE

Rated current: 32 A IP67 or IP66/IP67

3P+PE

61242 PCE / ELCEE / IDE

Rated current: 32 A IP67 or IP66/IP67

3P+PE

60252 PCE / ELCEE / IDE

Rated current: 32 A IP67 or IP66/IP67

3P+N+PE

61252 PCE / ELCEE / IDE

Rated current: 32 A IP67 or IP66/IP67 3P+N+PE







Date: 2023 03 06 Page 4 of 5

#### Type code

Housing   Blank   Without knock-outs   With knock-outs   With knock-outs   Blank   With knock-outs   Blank   With knock-outs   Blank   Nickel plated contacts   Blank   Indicating colour   Widnight-series   Reserved for additional colours												Тур	e code				
blank   Without knock-outs	60	2	3	2	:	-	6	*	*	*							
blank   Without knock-outs											_						
blank   Without knock-outs												Housing					
Rated current   Sicker   Sic																	
Contacts   blank   Nickel plated contacts   blank   Nickel plated contacts																	
Diank   Nickel plated contacts   Diank   Uncoated contacts   Diank   Indicating colour   Xs   Midnight-series   Reserved for additional colours   Diank   Nickel plate																	
Diank   Nickel plated contacts   Diank   Uncoated contacts   Diank   Indicating colour   Xs   Midnight-series   Reserved for additional colours   Diank   Nickel plate												Contacts					
Discrete   Discrete									L								
blank   Indicating colour												_					
blank   Indicating colour																	
blank   Indicating colour												Colour					
XS   Midnight-series     Reserved for additional colours								-					Indicating colour				
Reserved for additional colours																	
Clock position earthing contact																	
1																	
1												Clock p	osition earthing contact				
3   3   h   4   4   h   5   5   5   h   6   6   h   7   7   h (not available for 3-poles)   9   9   h   11   11   h   12   12   h												1					
4												3					
S   5 h   6   6 h   7   7 h (not available for 3-poles)   9   9 h   11   11 h   12   12 h																	
G   6 h   7   7 h (not available for 3-poles)   9   9 h   11   11 h   12   12 h												5					
Total not available for 3-poles   9																	
9   9 h   11   11 h   12   12 h												7					
11												9					
Customer type   -   Trademark PCE																	
Customer type																	
Degree of protection     blank   IP44 or IP44/IP54     2   IP67 or IP66/IP67     Poles     3   3-poles     4   4-poles     5   5-poles     Rated current     2   32 A     Ground type     60   Panel-type switched socket outlet																	
Degree of protection     blank   IP44 or IP44/IP54     2   IP67 or IP66/IP67     Poles     3   3-poles     4   4-poles     5   5-poles     Rated current     2   32 A     Ground type     60   Panel-type switched socket outlet												Custom	ner type				
Degree of protection     blank   IP44 or IP44/IP54     2   IP67 or IP66/IP67     Poles     3   3-poles     4   4-poles     5   5-poles     Rated current     2   32 A     Ground type     60   Panel-type switched socket outlet												-					
blank   IP44 or IP44/IP54     2													-				
blank												Degree of protection					
Poles   3   3-poles   4   4-poles   5   5-poles				L													
Poles  3 3-poles 4 4-poles 5 5-poles  Rated current 2 32 A  Ground type 60 Panel-type switched socket outlet																	
3   3-poles     4   4-poles     5   5-poles																	
3   3-poles     4   4-poles     5   5-poles												Poles					
4 4-poles 5 5-poles  Rated current 2 32 A  Ground type 60 Panel-type switched socket outlet													3-poles				
Rated current 2 32 A  Ground type 60 Panel-type switched socket outlet																	
Rated current 2 32 A  Ground type 60 Panel-type switched socket outlet													5-poles				
2 32 A  Ground type  60 Panel-type switched socket outlet																	
2 32 A  Ground type  60 Panel-type switched socket outlet												Rated c	urrent				
Ground type  60 Panel-type switched socket outlet																	
60 Panel-type switched socket outlet																	
60 Panel-type switched socket outlet											Ground type						
												_					
To Tourido typo difficitod doditot												61	Surface-type switched socket outlet				







Date: 2023 03 06 Page 5 of 5

# Typelist

Туре	Rated current A	Earthing contact pos. h	Rated operating voltage V	Frequency Hz	Insulation voltage V
		1	Other ratings	Other ratings	690
6023		4	100 – 130	50 and 60	690
6123	32	6	200 – 250	50 and 60	690
60232	32	9	380 – 415	50 and 60	690
61232		12	Supply from an isolating transformer	50 and 60	690
		1	Other ratings	Other ratings	690
		3	380 440	50 60	690
6024		4	100 – 130	50 and 60	690
6124		5	600 – 690	50 and 60	690
60242	32	6	380 – 415	50 and 60	690
61242		7	480 - 500	50 and 60	690
01272		9	200 – 250	50 and 60	690
		11	440 – 460	60	690
		12	Supply from an isolating transformer	50 and 60	690
		1	Other ratings	Other ratings	690
		3	220/380 250/440	50 60	690
COSE		4	57/100 – 75/130	50 and 60	690
6025 6125		5	347/600 – 400/690	50 and 60	690
60252	32	6	200/346 – 240/415	50 and 60	690
61252		7	277/480 – 288/500	50 and 60	690
31202		9	120/208 – 144/250	50 and 60	690
		11	250/440 – 265/460	60	690
		12	Supply from an isolating transformer	50 and 60	690

