

|                        |   |
|------------------------|---|
| article#               | <b>0152-6xv</b>   |
| article description    | <b>CEE-plug 16A 5p 6h IP67 SHARK black</b>  |
| description long       | CEE-plug 16A 5p 6h IP67 SHARK black<br>housing material: PA6<br>rated current: 16A<br>number of poles: 5 (3P+N+PE)<br>clock-position: 6h<br>rated voltage/frequency: 200/346V~ - 240/415V~/50+60Hz<br>contacts: brass nickel plated<br>connection technology: screw terminals<br>IP protection class: IP66/IP67 |
| GTIN (EAN)             | 9003399597305   |
| country of origin      | AT  |
| customs number         | 85366990  |
| net weight             | 0.183 kg  |
| packaging quantity     | 10  |
| minimum order quantity | 10  |

|                                 |                      |
|---------------------------------|----------------------|
| ETIM 9.0                        | EC000140             |
| IEC-amperage                    | 16 A                 |
| Number of poles                 | 5                    |
| Voltage according to EN 60309-2 | 400 V (50+60 Hz) red |
| Clock hour position             | 6 h                  |
| Identification colour           | Red                  |
| RAL-number                      | 9005                 |
| Degree of protection (IP)       | IP67                 |
| Connection system               | Screwed terminal     |
| Cable entry                     | Gland nut            |
| Angle of plug                   | Straight             |
| Material                        | Plastic              |
| Contact material                | CuZn                 |
| Surface treatment contacts      | Nickel-plated        |

|                        |                       |
|------------------------|-----------------------|
| a                      | 134                   |
| b                      | 87                    |
| K (cable Ø)            | 8-16 mm               |
| SW                     | 42 mm                 |
| wire flexible          | 1-2,5 mm <sup>2</sup> |
| contact screws         | 100 Ncm               |
| strain relief          | 500 Ncm               |
| dismantling length     | 50 mm                 |
| stripping length       | 10-12 mm              |
| ambient temperature    | -25 – 40 °C           |
| temperature resistance | -25 – 80 °C           |



<https://www.pcelectric.at/shop/en/?func=detail&artnr=0152-6xv>