

|                        |  |
|------------------------|--|
| article#               | <b>0239-6v</b>   |
| article description    | <b>CEE-plug 30A 2P3W 6h IP44 UL</b>  |
| description long       | CEE-plug 30A 2P3W 6h IP44 UL (PCE330P6Sv)<br>housing material: PA6<br>rated current: 32A/30A<br>number of poles: 2P3W (3p)<br>clock position: 6h<br>rated voltage: 250Vac<br>contacts: brass nickel plated<br>connection technology: screw terminals<br>IP protection class: IP44<br>according to UL1682 und IEC/EN 60309-2 (SERIE II)<br>UL-product category: QLHN / QLHN7<br>UL-file number: E232901 |
| GTIN (EAN)             | 9003399934902  |
| country of origin      | AT   |
| customs number         | 85366990   |
| net weight             | 0.181 kg   |
| packaging quantity     | 10   |
| minimum order quantity | 10   |

|   |                  |
|---|------------------|
| ETIM 9.0                                      | EC000140         |
| IEC-amperage                                  | 32 A             |
| Amperage according to UL/CSA (for UL-version) | 30 A             |
| Number of poles                               | 3                |
| Clock hour position                           | 6 h              |
| Identification colour                         | Blue             |
| Degree of protection (IP)                     | IP44             |
| Connection system                             | Screwed terminal |
| Cable entry                                   | Gland nut        |
| Angle of plug                                 | Straight         |
| Material                                      | Plastic          |
| Contact material                              | CuZn             |
| Surface treatment contacts                    | Nickel-plated    |

|                        |                |
|------------------------|----------------|
| a                      | 5.91 inch      |
| b                      | 4.09 inch      |
| c                      | 2.48 inch      |
| K (cable Ø)            | 0.52-0.76 inch |
| SW                     | 1.97 inch      |
| wire flexible          | 14-10 AWG      |
| contact screws         | 9.74 lbf-in    |
| strain relief          | 62.0 lbf-in    |
| dismantling length     | 1.97 inch      |
| stripping length       | 0.47-0.55 inch |
| temperature resistance | -13 – 176 °F   |



<https://www.pcelectric.at/shop/en/?func=detail&artnr=0239-6v>

