


| | |
|------------------------|--|
| article# | 2232-1 |
| article description | CEE-connector 32A 3p 1h IP67 SHARK |
| description long | CEE-connector 32A 3p 1h IP67 SHARK housing material: PA6 rated current: 32A number of poles: 3 (2P+PE) clock-position: 1h rated voltage/frequency: >50V / others contacts: brass connection technology: screw terminals IP protection class: IP66/IP67 |
| GTIN (EAN) | 9003399392153 |
| country of origin | AT |
| customs number | 85366990 |
| net weight | 0.275 kg |
| packaging quantity | 10 |
| minimum order quantity | 10 |

| | |
|---------------------------------|------------------|
| ETIM 9.0 | EC001320 |
| IEC-amperage | 32 A |
| Number of poles | 3 |
| Voltage according to EN 60309-2 | Other |
| Clock hour position | 1 h |
| Identification colour | Grey |
| Degree of protection (IP) | IP67 |
| Connection system | Screwed terminal |
| Angle of plug | Straight |
| Cable entry | Gland nut |
| Material | Plastic |
| Contact material | CuZn |
| Surface treatment contacts | Untreated |

| | |
|------------------------|-----------------------|
| a | 163 mm |
| b | 96 mm |
| K (cable Ø) | 11,5-20 mm |
| SW | 50 mm |
| wire flexible | 2,5-6 mm ² |
| contact screws | 110 Ncm |
| strain relief | 600 Ncm |
| dismantling length | 50 mm |
| stripping length | 12-14 mm |
| ambient temperature | -25 – 40 °C |
| temperature resistance | -25 – 80 °C |







<https://www.pcelectric.at/shop/en/?func=detail&artnr=2232-1>