


article#	<b>2445-6</b>
article description	<b>CEE-connector 125A 4p 6h IP67 pilot contact POWER TWIST</b>
description long	CEE-connector 125A 4p 6h IP67 POWER TWIST housing material: PA6 rated current: 125A number of poles: 4 (3P+PE) clock-position: 6h rated voltage/frequency: 380-415V~ / 50+60Hz contacts: brass, with lamellar spring (CuBe) connection technology: frame terminals with screws IP protection class: IP66/IP67  Extra: pilot contact with screw terminal (rated current 2A)
GTIN (EAN)	9003399027277
country of origin	AT
customs number	85366990
net weight	1.220 kg
packaging quantity	2
minimum order quantity	2



ETIM 9.0	EC001320
IEC-amperage	125 A
Number of poles	4
Voltage according to EN 60309-2	380-415 V (50+60 Hz) red
Clock hour position	6 h
Identification colour	Red
RAL-number	7046
Degree of protection (IP)	IP67
Connection system	Screwed terminal
Angle of plug	Straight
Cable entry	Gland nut
Material	Plastic
Contact material	CuZn
Surface treatment contacts	Untreated



a	287 mm
b	124 mm
K (cable Ø)	22,5-50 mm
SW	81 mm
wire flexible	16-50 / 1-2,5 (pilot contact) mm <sup>2</sup>
contact screws	450 / 100 (pilot contact) Ncm
connecting screws	200 Ncm
strain relief	1500 Ncm
dismantling length	100 mm
stripping length	24-27 mm
ambient temperature	-25 – 40 °C
temperature resistance	-25 – 80 °C





<https://www.pcelectric.at/shop/en/?func=detail&artnr=2445-6>

