


article#	245-1
article description	CEE-connector 125A 5p 1h IP67 POWER TWIST
description long	CEE-connector 125A 5p 1h IP67 POWER TWIST housing material: PA6 contact frame with screws contacts: brass with CuBe lamellar spring protection degree: IP66/67 watertight
GTIN (EAN)	9003399084256
country of origin	AT
customs number	85366990
net weight	1.266 kg
packaging quantity	2
minimum order quantity	2

ETIM 9.0	EC001320
IEC-ampereage	125 A
Number of poles	5
Voltage according to EN 60309-2	Other
Clock hour position	1 h
Identification colour	Grey
Degree of protection (IP)	IP67
Connection system	Screwed terminal
Angle of plug	Straight
Cable entry	Gland nut
Material	Plastic
Contact material	CuZn
Surface treatment contacts	Untreated

a	287 mm
b	124 mm
K (cable Ø)	22,5-50 mm
SW	81 mm
wire flexible	16-50 mm ²
contact screws	450 Ncm
connecting screws	200 Ncm
strain relief	1500 Ncm
dismantling length	100 mm
stripping length	24-27 mm
ambient temperature	-25 – 40 °C
temperature resistance	-25 – 80 °C



<https://www.pcelectric.at/shop/en/?func=detail&artnr=245-1>