

article#	353463P
article description	Wallbox GLB+ 22kW, charging socket Type2, 4G+RFID
description long	Wallbox GLB+ Charging Station for Electric Vehicles Connection: (230)400V AC, 50Hz, (1)3-phasing Number of charging units: 1 Socket outlet Type 2 with locking actuator Max. power per charging point: 22kW Charging current (min-max): 6A - 32A Nominal connection power: 22kW Protection: DC-fault protection (6mA) Access control: RFID Controller: CC612 charge controller Communication interface: 4G Module Communication: OCPP 1.6 JSON, Modbus TCP Backend system: no preconfiguration WxHxD: 205x422x124 mm Material housing: plastic/ black Lockable cover Mounting method: Wall mounting Degree of protection: IP44 Impact strength: IK08 Ambient temperature: -25°C bis +40°C integrated digital modbus energy meter, certified acc. to MID directive Standards: EN 61851-1, IEC 61439-7
GTIN (EAN)	9003399448782
country of origin	PL
customs number	85371098
net weight	3.200 kg
minimum order quantity	1

ETIM 9.0	EC002883
Installation side connection model	3-phase
Input voltage	230 – 400 V
Frequency	50 Hz
Nominal connection power	22 kW
Number of charging units	1
Max. power per charging point	22 kW
Width	205 mm
Height	422 mm
Depth	124 mm
Mounting method	Wall mounting
Number of socket outlets Type 2	1
Charging cable permanently lockable at charging device	True
DC residual current detection	True
Contactor welding detection	False
With circuit breaker	False
Network-enabled as a master	True
Network-enabled as an extender	True
Networkable via LAN	True
Networkable via Wi-Fi	False
LTE	True
With energy meter	True
With built-in RFID card reader	True
NFC (Near Field Communication)	True
Static load management integrated	False
Suitable for dynamic load management	True
Open Charge Point Protocol (OCPP) version	1.6



<https://www.pcelectric.at/shop/en/?func=detail&artnr=353463P>