

article#	<b>3539840101P</b>
article description	<b>TWINBOX PCE GTB+ T2DO22 4G Z RF bEsingle</b>
description long	<p>TWINBOX GTB+ Charging Station for Electric Vehicles                      Connection: (230)400V AC, 50Hz, (1)3-phases                      Number of charging units: 2                      Socket outlet Type 2 with locking actuator                      Max. power per charging point: 22kW                      Nominal connection power: 44kW                      WxHxD: 377x660x213 mm                      Mounting method: Wall mounting                      Protection:                      RCCB Type A + integr. DC-fault protection (6mA)                      MCB C 32A 4 pole                      Access control: RFID                      Controller: CC612 charge controller                      Communication interface: 4G-modules                      Communication: OCPP 1.6 JSON, Modbus TCP                      Backend system: preconfiguration                      be.ENERGISED for immediate start-up                      integrated digital modbus energy meter, certified acc. to MID directive                      Material housing: aluminium / black                      Degree of protection: IP44                      Impact strength: IK10                      Ambient temperature: -25°C bis +40°C                      Standards: EN 61851-1, IEC 61439-7</p> <p>be.ENERGISED Monitoring Package Single                      104046701                      1 pc. configuration instructions                      1 pc. SIM card, 2 pcs. QR code                      1 pc. instructions for activation, 2 pcs. RFID tags</p>
GTIN (EAN)	9003399528569
country of origin	SE
customs number	85371098
net weight	24.500 kg
packaging quantity	0
minimum order quantity	1

ETIM 9.0	EC002883
Installation side connection model	3-phase
Input voltage	400 – 400 V
Frequency	50 Hz
Nominal connection power	44 kW
Number of charging units	2
Max. power per charging point	22 kW
Width	377 mm
Height	660 mm
Depth	213 mm
Mounting method	Wall mounting
Number of socket outlets Type 2	2
Number of earth leakage circuit breakers type A	2
Charging cable permanently lockable at charging device	True
DC residual current detection	True
Contactor welding detection	False
With circuit breaker	True
Network-enabled as a master	True
Network-enabled as an extender	False
Networkable via LAN	True
Networkable via Wi-Fi	True
LTE	True
With energy meter	True
With built-in RFID card	True

reader	
NFC (Near Field Communication)	True
Static load management integrated	False
Suitable for dynamic load management	True
Open Charge Point Protocol (OCPP) version	1.6



<https://www.pcelectric.at/shop/en/?func=detail&artnr=3539840101P>

