

| | |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| article# | 80252-10v |
| article description | CEE angled plug 32A 5p 10h IP67 TWIST |
| description long | CEE angled plug 32A 5p 10h IP67 TWIST housing material: PC/ABS rated current: 32A number of poles: 5 (3P+N+PE) clock-position: 10h rated voltage/frequency: >50V~ / 100-300Hz contacts: brass nickel plated connection technology: screw terminals IP protection class: IP67 |
| country of origin | AT |
| customs number | 85366990 |
| packaging quantity | 10 |
| minimum order quantity | 10 |

| | |
|---------------------------------|-----------------------------|
| ETIM 9.0 | EC000140 |
| IEC-amperage | 32 A |
| Number of poles | 5 |
| Voltage according to EN 60309-2 | 50-500 V (100-300 Hz) green |
| Clock hour position | 10 h |
| Identification colour | Green |
| Degree of protection (IP) | IP67 |
| Connection system | Screwed terminal |
| Cable entry | Gland nut |
| Angle of plug | Angled |
| Material | Plastic |
| Contact material | CuZn |
| Surface treatment contacts | Nickel-plated |

| | |
|------------------------|-----------------------|
| a | 136 mm |
| b | 100 mm |
| c | 118 mm |
| d | 25 ° |
| K (cable Ø) | 11,5-22 mm |
| SW | 50 mm |
| wire flexible | 2,5-6 mm ² |
| contact screws | 110 Ncm |
| strain relief | 600 Ncm |
| dismantling length | 50 mm |
| stripping length | 12-14 mm |
| ambient temperature | -25 – 40 °C |
| temperature resistance | -25 – 80 °C |



<https://www.pcelectric.at/shop/en/?func=detail&artnr=80252-10v>